

Abstract Submitted  
for the DFD12 Meeting of  
The American Physical Society

**3D Droplet velocities and sizes in the Ranque-Hilsch vortex tube<sup>1</sup>**

R. LIEW, J.C.H. ZEEGERS, Department of Applied Physics, Eindhoven University of Technology, J.G.M. KUERTEN, Faculty EEMCS, University of Twente, W.R. MICHALEK, Department of Mechanical Engineering, Eindhoven University of Technology — The Ranque-Hilsch vortex tube is a known device that is used to generate spot cooling. In this study, we experimentally investigate the behavior of small water droplets in the vortex tube by means of Phase Doppler Particle Analysis. In an experimental vortex tube, droplets were injected together with a carrier gas to form a fast rotating (up to 80.000 rpm) droplet-gas mixture. Droplet sizes, 3D velocity components, and turbulent properties were measured, showing high intensity isotropic turbulence in the core region. To investigate the cause of the high intensity turbulence, a frequency analysis was applied on the measured velocity. The frequency spectrum of the velocity is presented and indicates that wobbling of the vortex axis is the cause of the high turbulence intensity. It was expected that larger droplets have a higher radial velocity because of the larger centrifugal force. Results show, however, that small and larger droplets behave similar.

<sup>1</sup>This research is supported by the Dutch Technology Foundation STW, which is the applied science division of NWO, and the Technology Programme of the Ministry of Economic Affairs.

Raoul Liew  
Eindhoven University of Technology

Date submitted: 31 Jul 2012

Electronic form version 1.4