

Abstract Submitted
for the DFD12 Meeting of
The American Physical Society

Drag Control through Wrinkling on Curved Surfaces¹ DENIS TERWAGNE, Department of Civil and Environmental Engineering, Massachusetts Institute of Technology, MA, USA, PEDRO REIS, Department of Mechanical Engineering and Department of Civil and Environmental Engineering, Massachusetts Institute of Technology, MA, USA — We present the results of an experimental investigation on the wrinkling of positively curved surfaces and explore their use towards drag reduction applications. In our precision desktop-scale experiments we make use of rapid prototyping techniques to cast samples with custom geometry and material properties out of silicone-based rubbers. Our structures consist of a thin stiff shell that is chemically bonded to a thicker soft substrate. The substrate contains a spherical cavity that can be depressurized, under controlled volume conditions, to compress the ensemble structure. Under this compressive loading, the initially smooth outer-shell develops complex wrinkling patterns. We systematically characterize and quantify the morphology of the various patterns and study the phase diagram of the system. We consider both geometric and material quantities in the parameter space. Moreover, since the wrinkling patterns can be actuated dynamically using a pressure signal, we systematically characterize the aerodynamic behavior of our structures in the context of fluid drag reduction. An added advantage of the novel mechanism we introduce is that it allows for both dynamic switching and tuning of the surface morphology, thereby opening paths for drag control.

¹D.T. thanks the B.A.E.F., the Fulbright Program and the WBI.World grants program for financial support.

Denis Terwagne
Massachusetts Institute of Technology, USA

Date submitted: 02 Aug 2012

Electronic form version 1.4