

Abstract Submitted
for the DFD12 Meeting of
The American Physical Society

Dynamic mode decomposition of H-type transition to turbulence¹

TARANEH SAYADI, JOSEPH NICHOLS, Center for Turbulence Research (CTR), Stanford, PETER SCHMID, LadHyX - CNRS - Ecole Polytechnique, PARVIZ MOIN, Center for Turbulence Research (CTR), Stanford — Dynamic mode decomposition (DMD) [1] is applied to a direct numerical simulation database of H-type transition to turbulence of a compressible, nominally-zero-pressure-gradient, spatially developing flat-plate boundary layer. The objective of this work is to identify the structures of dynamical importance throughout the transition region. DMD, viewed as an optimal phase averaging process in the context of the triple decomposition [2], is employed to assess the contribution of each coherent structure to the total Reynolds shear stress. In this region, it is observed that the total Reynolds shear stress gradient can be estimated accurately from only a few low-frequency DMD modes. These low-frequency modes are observed to correspond to the legs of hairpin vortices. Furthermore, DMD is applied to a large-eddy simulation (LES) database of the same configuration, generated using the dynamic Smagorinsky subgrid-scale model. The low-frequency DMD modes extracted from the LES, are, however, of lower amplitude than in the DNS, resulting in an underprediction of the Reynolds shear stress gradient and corresponding skin-friction coefficients.

[1] Schmid, P. J. JFM, 1-24, 2010.

[2] Reynolds, W. C. and Hussain, A. K. M. F. JFM, **54**, 236-288, 1972.

¹Supported by the PSAAP program of DoE

Taraneh Sayadi
Center for Turbulence Research (CTR), Stanford

Date submitted: 10 Aug 2012

Electronic form version 1.4