

Abstract Submitted
for the DNP16 Meeting of
The American Physical Society

Assembling, cleaning, and testing a unique prototype open-ended cylindrical penning trap¹ KASSIE MARBLE, Tarleton State University, PRAVEEN SHIDLING, DAN MELCONIAN, Texas AM Cyclotron Institute — A new experimental beamline containing a prototype cylindrical penning trap has recently been constructed at the Cyclotron Laboratory at Texas A&M University. The new beamline will enable precision experiments that enhance our understanding of the limits on non-SM processes in the weak interaction through the measurement of the β - ν correlation parameter for $T = 2$, $0^+ \rightarrow 0^+$ super allowed β -delayed proton emitters. The prototype TAMU TRAP consists of an open-ended cylindrical penning trap of diameter of 90 mm with gold-plated electrodes of oxygen free high conductivity copper to prevent oxidation. The trap's electric quadrupole field is provided by a SHIP TRAPS RF electronic circuit to the four segmented electrodes at the center of the trap while the trap's 7 Tesla radial magnetic field is provided by an Agilent 210 ASR magnet. A discussion of the assembly of the prototype TAMU TRAP, construction of the RF electronic circuit, the experimental set up and alignment of the beamline will be presented. The method used to test the prototype penning trap using an ion source, Faraday cups, and Micro Chanel Plate (MCP) detectors will also be discussed.

¹Work supported by the U.S. Department of Energy under Grant No. DE-FG02-11ER41747 and the National Science Foundation.

Kassie Marble
None

Date submitted: 25 Jul 2016

Electronic form version 1.4