

Abstract Submitted
for the DPP05 Meeting of
The American Physical Society

Low Voltage Beam Experiments on the PLIA. J. COLEMAN, P. ROY, F. BIENIOSEK, W. WALDRON, E. HENESTROZA, S. YU, LBNL, Berkeley, CA 94720, R. BRIGGS, SAIC, Alamo, CA 94507, LBNL COLLABORATION, SAIC COLLABORATION¹ — A new accelerator concept called the Pulse-Line Ion Accelerator (PLIA) has been developed. The PLIA operates as a transmission line with pulsed power sources generating a ramped traveling voltage wave on a helical coil. The oil dielectric helix has the ability to accelerate ion bunches to energies much greater than the peak applied voltage and over distances much larger than the ramp length. Low voltage beam experiments ranging from 10-80 kV have begun on the 1-m PLIA test section to verify the ability to accelerate an ion bunch and to investigate breakdown issues. Short-pulsed, pencil-like beams with energy ranges of 200-400 keV have been used for the acceleration experiments. Discharge issues have been addressed and evaluated for possible solutions. A semi-conductive chromium oxide film with a low secondary emission coefficient will be tested for elimination of the discharge. It is expected that the discharge issues will be resolved and beam experiments with high voltages will commence. Different acceleration scenarios will be examined relative to the axial focusing requirements. Experimental results and possible solutions for the elimination of the discharge will be described. (This work was supported by DOE under Contract No. DE-AC02-05CH11231).

¹HIF-VNL Collaboration

Joshua Coleman
Lawrence Berkeley National Laboratory, Berkeley, CA 94720

Date submitted: 21 Jul 2005

Electronic form version 1.4