Abstract Submitted for the DPP05 Meeting of The American Physical Society

Upgrades to the DIII-D Facility during the Long Torus Opening Activities Period in FY05-06¹ J.F. TOOKER, P.I. PETERSEN, General Atomics, DIII-D TEAM — During FY05 and FY06 the DIII-D facility has put its normal two periods for construction, refurbishment and maintenance back to back in order to establish a sufficiently long period to make major hardware upgrades. These upgrades, which are driven by physics needs, include modifying the lower divertor, rotating one of the existing four neutral beam lines, and adding three 1 MW long pulse gyrotrons. The new lower divertor will allow pumping of high triangularity plasmas needed to study the ultimate performance of highly shaped plasmas. There are several motivations for rotating one of the neutral beam lines: the physics of plasma rotation, QDB regime with central co-rotation, RWM stability with low rotation, etc. The long pulse gyrotrons will replace the aging short pulse Russian gyrotrons. In addition to these high priority tasks, we will start upgrade of the toroidal coil return bus and upgrade and modernize the infrastructure, which includes replacing two cooling towers and installing a new high voltage transformer for the auxiliary heating systems.

¹Work supported by U.S. DOE under DE-FC02-04ER54698.

T.S. Taylor

Date submitted: 22 Jul 2005 Electronic form version 1.4