Abstract Submitted for the DPP06 Meeting of The American Physical Society

**Optimization Studies of a Multi-GeV Single Stage Laser-Plasma Accelerator**<sup>1</sup> G.M. TARKENTON, Institute for Advanced Physics, B.A. SHAD-WICK, LOASIS Program, LBNL and Institute for Advanced Physics, C.B. SCHROEDER, LOASIS Program, LBNL, E. ESAREY, LOASIS Program, LBNL — Using a self-consistent Hamiltonian model of beam transport in a background plasma<sup>2</sup>, we consider the design of a single stage, multi-GeV plasma accelerator. In this model the beam is described by phase-space moments and the bulk plasma is taken to be a cold fluid. We present a detailed study of beam propagation in a resonant laser-wakefield accelerator with final energy gain between 5 and 10 GeV. We discuss optimization of the system with regard to energy gain and beam quality.

<sup>1</sup>Supported by the US DoE contract DE-AC02-05CH11231 and by the Institute for Advanced Physics

<sup>2</sup>B. A. Shadwick, G. M. Tarkenton and C. B. Schroeder, Bull. Am. Phys. Soc., **50**, 283 (2005).

B. Shadwick LOASIS Program, LBNL

Date submitted: 26 Jul 2006

Electronic form version 1.4