

Abstract Submitted  
for the DPP06 Meeting of  
The American Physical Society

**Measurement of  ${}^3\text{He}({}^3\text{He},2\text{p}){}^4\text{He}$  Reactions in an IEC Device<sup>1</sup>**

GREGORY R. PIEFER, GILBERT A. EMMERT, JOHN F. SANTARIUS, Univ. of Wisconsin — An inertial electrostatic confinement (IEC) device has been used to measure  ${}^3\text{He}({}^3\text{He},2\text{p}){}^4\text{He}$  reactions. The experimental setup consists of a spherical vacuum vessel approximately 61 cm in diameter held at ground potential and a spherical cathode centered within the vessel that can be biased from 0 to -200kV. The ion source is an externally mounted high-density helicon source which provides a beam of up to  $\sim 6 \times 10^{16}$  ions/s. This source allows for IEC operation to occur at  ${}^3\text{He}$  background pressures of  $< 0.02$  Pa, reducing atomic effects and allowing for more straightforward code validation. An integral equation approach models atomic physics processes and nuclear reactions in order to predict the energy spectrum of the  ${}^3\text{He}$  ions (details in poster by Emmert and Santarius, this conference). The integral equation is solved numerically by finite differences. The  ${}^3\text{He}({}^3\text{He},2\text{p}){}^4\text{He}$  fusion reaction rates measured experimentally will be compared to those generated by the computer code.

<sup>1</sup>Research supported by the Dept. of Energy, the Univ. of Wisconsin, and the Greatbatch Foundation

John F. Santarius  
Univ. of Wisconsin

Date submitted: 24 Jul 2006

Electronic form version 1.4