

Abstract Submitted  
for the DPP07 Meeting of  
The American Physical Society

**Modeling High-Energy Backlighters Produced by Intense Laser-Matter Interaction**<sup>1</sup> GREGORY POLLAK, Los Alamos National Laboratory — The utility of reasonably monoenergetic, high frequency backlighters for radiographic use in high energy density physics experiments has been understood for a long time. A reasonable approach to generating these xrays is to use a high-intensity laser incident on suitable (typically mid-z) elements. The deposition produces hot (non-thermal) electrons and ions, which ionize and excite inner shell electrons in a highly non-LTE environment. Resulting xray generation often occurs in only a few bound-bound transitions. Because the hot electrons have substantial range, the lines can be optically thick. In this presentation, I use the radhydro code Lasnex to deposit both a prepulse and a main pulse of order  $10^{18}$  to  $10^{19}$  watts/cm<sup>2</sup> onto Ag and Sn substrates. The physical situation is then postprocessed using Plaspp, with an embedded DCA package to produce spectra. A unique feature of these simulations are the multiphoton inverse-bremsstrahlung and photoionization physics for deposition near the critical surface, as well as non-thermal collisional physics for the non-LTE spectra.

<sup>1</sup>Work supported by USDOE, performed at LANL, under contract DE-AC52-06NA25396

Gregory Pollak  
Los Alamos National Laboratory

Date submitted: 19 Jul 2007

Electronic form version 1.4