

Abstract Submitted
for the DPP07 Meeting of
The American Physical Society

Status of RF Heating and Current Drive Systems for KSTAR

YOUNG-SOON BAE, National Fusion Research Center, JIN-HYUN JEONG, SEUNG-IL PARK, MOO-HYUN CHO, WON NAMKUNG, Pohang University of Science and Technology, JONG-GU KWAK, JAE-SUNG YOON, YEONG-DUK BAE, SON-JONG WANG, SUK-KWON KIM, CHUL-KEW HWANG, SUNG-KYU KIM, Korea Atomic Energy Research Institute — The heating and current drive systems consisting of neutral beam injection (NBI) and radio frequency (RF) systems will be used for the KSTAR whose construction will be completed by August, 2007. The KSTAR RF heating and current drive systems are composed of ion cyclotron range of frequencies (ICRF), lower hybrid current drive (LHCD) system, and electron cyclotron heating (ECH) system. The KSTAR adopts the ECH-assisted start-up for the flexibility and reliability of the operation regime using 84 GHz, 500 kW gyrotron. For the KSTAR first plasma scheduled at June, 2008, two RF heating systems, 84 GHz ECH and 25-60 MHz ICRF systems, will be used for the pre-ionization to reduce the loop voltage and the wall discharge cleaning, respectively. This paper describes the status of the KSTAR RF heating and current drive systems and the initial test results using dummy load. Also, the upgrade plan of the KSTAR RF heating and current drive systems will be presented as well as the key features and the relevant technological issues for the long pulse operation.

Young-Soon Bae
National Fusion Research Center

Date submitted: 31 Jul 2007

Electronic form version 1.4