

Abstract Submitted
for the DPP08 Meeting of
The American Physical Society

Improved non-LTE simulation algorithm¹ MICHEL BUSQUET²,
MARCEL KLAPISCH, ARTEP, Inc., Ellicott City, MD, DENIS COLOMBANT,
Plasma Physics Division, NRL, Washington, DC, DAVID FYFE, LCP-FD, NRL,
Washington, DC, JOHN GARDNER, Berkeley Research Associates, Springfield, VA
— The RAdiation Dependent Ionization Model (RADIOM)- a.k.a Busquet’s model-
[1] has proven its success in simulating non –LTE effects in laser fusion plasmas [2].
This improved algorithm can take into account Auger effect by a new parameter
fitted to SCROLL [3] results. It is independent of the photon binning thanks to a
projection on a standard grid. It guarantees smoother convergence to LTE. This
algorithm has been implemented in a new way in the hydro-code FASTnD. Hydro
simulations on the recent subMJ targets[4], with and without non-LTE corrections
will be shown. [1] M. Busquet, Phys. Fluids B 5, 4191(1993). [2] D.G. Colombant
et al. . . , Phys. Plas. 7,2046 (2000). [3] A. Bar-Shalom, J. Oreg M. Klapisch, J.
Quant. Spectr. Rad. Transf. **65** ,43 (2000). [4] S. P. Obenschain, D. G. Colombant,
A. J. Schmitt et al., Phys. Plasmas **13**, 056320 (2006).

¹Work supported By USDOE through a contract with Laser Plasma Branch, NRL.

²Also Observatoire de Paris-LERMA, France

Michel Busquet
ARTEP, Inc., Ellicott City, MD

Date submitted: 17 Jul 2008

Electronic form version 1.4