

Abstract Submitted
for the DPP08 Meeting of
The American Physical Society

Measurements of the Non-Linear Coupling of Plasma Waves¹ E.K. SNIPES, Wittenberg Univ., J. MCCLENAGHAN, A.J. NOBLE, A.A. KABANTSEV, C.F. DRISCOLL, UCSD — A separatrix is created in a pure electron plasma column by applying a θ -symmetric wall voltage. This “squeeze” voltage traps less energetic electrons in either end and allows more energetic electrons to pass through. These trapped particles enable the novel Trapped Particle Diocotron Mode (TPDM). We excite an ordinary $m = 2$ diocotron mode at frequency f_2 to amplitude A_2 and observe the decay into the $m = 1$ TPDM at $f_1 \approx f_2/2$. The exponential growth rate, Γ , of the TPDM is obtained as a function of the amplitude A_2 as well as a function of the “squeeze” voltage which determines the frequency mismatch $\delta f = f_2/2 - f_1$. We calibrate the amplitudes of the modes in terms of the received wall voltages, and obtain a quantitative value of the non-linear coupling coefficient, V . These results at $B = 280$ G will be compared to recent results² from a separate apparatus at $B > 2000$ G.

¹Supported by NSF/REU PHY-0552402 and NSF PHY-0354979.

²A.A. Kabantsev, T.M. O’Neil, Yu.A. Tsidulko, and C.F. Driscoll, Phys. Rev. Lett. **101**, 065002 (2008).

C. Fred Driscoll
UCSD

Date submitted: 13 Aug 2008

Electronic form version 1.4