

Abstract Submitted  
for the DPP09 Meeting of  
The American Physical Society

**Dependence of Bootstrap Current, Stability, and Transport on the Safety Factor Profile in DIII-D Steady-state Scenario Discharges**<sup>1</sup> C.T. HOLCOMB, LLNL, J.R. FERRON, T.C. LUCE, P.A. POLITZER, J.C. DEBOO, T.W. PETRIE, C.C. PETTY, R.J. LA HAYE, GA, A.E. WHITE, F. TURCO, ORISE, E.J. DOYLE, T.L. RHODES, L. ZENG, UCLA — A high beta, high gain steady state tokamak scenario with large bootstrap current fraction will have strong coupling between the current density and the pressure gradient through turbulent transport and the bootstrap current. To address this coupling experimentally, a scan of the safety factor minimum ( $q_{min}$ , from 1.1 to over 2) and edge value ( $q_{95}$ , from 4.5 to 6.5) was performed. The bootstrap current fraction increases with  $q_{min}$  and  $q_{95}$  by virtue of increasing density gradients. Compared to lower  $q_{min}$ ,  $q_{min} > 2$  has lower  $n = 1$  stability limits, enhanced drift wave growth rates, higher low- $k$  density fluctuations, and lower confinement. At  $q_{min} > 2$  and  $q_{95} = 4.5$  the unsustainable condition  $J_{BS} > J_{Total}$  occurs near the axis. These considerations suggest intermediate  $q$  is the optimal operating point.

<sup>1</sup>Work supported by the US DOE under DE-AC52-07NA27344, DE-FC02-04ER54698, DE-AC05-06OR23100, DE-FG03-08ER54984.

Chris Holcomb  
LLNL

Date submitted: 18 Jul 2009

Electronic form version 1.4