

Abstract Submitted  
for the DPP11 Meeting of  
The American Physical Society

**Upgrade Plans and Performance of the DIII-D ECH System<sup>1</sup>**

J. LOHR, M. CENGHER, Y.A. GORELOV, H.J. GRUNLOH, A.G. KELLMAN, C.J. PAWLEY, W. MCDANIEL, R.C. O'NEILL, D. PONCE, R. PRATER, J.F. TOOKER, General Atomics, R.A. ELLIS, PPPL, M. BLANCK, P. BORCHARD, K. FELCH, S. CAUFFMAN, CPI — An upgrade is in progress on the DIII-D gyrotron complex, to increase the number of gyrotrons from 6 to 8 and raise the injected rf power from 3.5 to 5.5 MW. The 1st step in this upgrade is the production of a depressed collector diode gyrotron planned for initial operation in early 2012 operating at 110 GHz and generating 1.2 MW, the same frequency as the existing gyrotrons. The 8th gyrotron for the complex is planned for completion in 2013. This gyrotron will operate at 117.5 GHz and generate 1.5 MW for a pulse length of 10 s. The upgrade includes a 4th dual launcher and new high voltage power supply. The present installation has been upgraded by rerouting the waveguide transmission lines to reduce the number of miter bends, increasing the scanning speed and pointing accuracy of the articulating launcher mirrors and providing for aiming scans, with feedback, during a plasma shot.

<sup>1</sup>Work supported in part by the US DOE under DE-FC02-04ER54698, DE-AC02-09CH11466, and GA IR&D funding.

John Lohr  
General Atomics

Date submitted: 25 Jul 2011

Electronic form version 1.4