

Abstract Submitted
for the DPP14 Meeting of
The American Physical Society

Time-Dependent DIII-D Heat Transport Simulations Using Neural-Network Models¹ J.M. PENNA, Massachusetts Institute of Technology, S.P. SMITH, General Atomics, O. MENEGHINI, Oak Ridge Associated Universities, C.J. LUNA, Arizona State University — The neural network transport model BRAINFUSE has been developed to produce transport fluxes based on local parameters [1]. The BRAIN-FUSE model has been integrated into the transport modeling framework ONETWO [2,3] in order to develop time dependent solutions and has been validated by artificially varying the input neutral beam power and comparing the output to DIII-D scans. These efforts have led to the development of a time-dependent workflow within the OMFIT integrated modeling framework. The new work flow can evolve the electron and ion temperatures as a function of time dependent sources and equilibria. The effects of different engineering parameters can be explored and optimized in support of DIII-D operations. The efficiency of this workflow enables planning plasma operations of next-day experiments, as will be required for ITER.

[1] O. Meneghini et al., Phys. Plasmas **21**, 060702 (2014).

[2] W.W. Pfeiffer et al., General Atomics Report GA-A16178 (2980).

[3] O. Meneghini et al., Bull. Am. Phys. Soc. **58**, 109 (2014).

¹Work supported in part by the National Undergraduate Fellowship Program in Plasma Physics and Fusion Energy Sciences and the US Department of Energy under DE-FG02-94ER54235 & DE-FC02-04ER54698.

Sterling Smith
General Atomics

Date submitted: 10 Jul 2014

Electronic form version 1.4