

Abstract Submitted
for the DPP16 Meeting of
The American Physical Society

A Novel Spherical Hohlräum Design with Tetrahedral 4 Laser Entrance Holes and High Radiation Performance.¹ LONGFEI JING, Research Center of Laser Fusion, China Academy of Engineering Physics, YUNBAO HUANG, mechatronics Engineering School of Guangdong University of Technology, SHAOEN JIANG, Research Center of Laser Fusion, China Academy of Engineering Physics, HAIYAN LI, mechatronics Engineering School of Guangdong University of Technology, TIANXUAN HUANG, YONGKUN DING, Research Center of Laser Fusion, China Academy of Engineering Physics — As usual cylindrical hohlraum with double laser ring cones may lead to serious CBET effect, spherical hohlraum with octahedral 6 LEHs and single laser ring cone is presented to achieve higher radiation symmetry during the fusion process. However, it has several potential problems such as the long run distance, smaller space is left for diagnose, and the assembly of centrally located capsule. In this paper, we investigate the radiation performance, i.e., radiation symmetry and drive temperature on the capsule in the spherical hohlraum with tetrahedral 4 LEHs and single laser ring cone, since there is more available space for laser disposition and diagnose. Then, such target is optimized on the laser beam pointing direction and shape sizes to achieve high radiation performance, or the radiation symmetry and drive temperature on the capsule. Finally, a novel spherical hohlraum with optimal laser beam pointing and shape size has been demonstrated to have almost similar radiation symmetry (the radiation asymmetry variation is no more than 0.2%), and higher drive temperature (the temperature has been increased by 1.73%, and additional 133 KJ energy of 2MJ energy for fusion can be utilized)..

¹This work was supported by NSAFU1430124, and NSFC51375185, 51405177, 11475154.

Yunbao Huang
mechatronics Engineering School of Guangdong University of Technology

Date submitted: 15 Jul 2016

Electronic form version 1.4