

Abstract Submitted
for the DPP17 Meeting of
The American Physical Society

View Factor and Radiation-Hydrodynamic Simulations of Gas-Filled Outer-Quad-Only Hohlräume at the National Ignition Facility¹

CHRISTOPHER YOUNG, NATHAN MEEZAN, OTTO LANDEN, Lawrence Livermore National Laboratory — A cylindrical National Ignition Facility hohlraum irradiated exclusively by NOVA-like [1] outer quads (44.5° and 50° beams) is proposed to minimize laser plasma interaction (LPI) losses and avoid problems with propagating the inner (23.5° and 30°) beams. Symmetry and drive are controlled by shortening the hohlraum, using a smaller laser entrance hole (LEH), beam phasing the 44.5° and 50° beams [2-3], and correcting the remaining P_4 asymmetry with a capsule shim [4]. Ensembles of time-resolved view factor simulations [5] help narrow the design space of the new configuration, with fine tuning provided by the radiation-hydrodynamic code HYDRA. [1] L. J. Suter, et al., Phys. Rev. Lett. 73, 2328 (1994). [2] R. E. Turner, et al., Phys. Plasmas 7, 333 (2000). [3] S. G. Glendinning, et al., Rev. Sci. Instrum. 70, 536 (1999). [4] D. S. Clark, et al., Phys. Plasmas 23, 072707 (2016). [5] J. J. MacFarlane, J. Quant. Spectr. Rad. Transfer 81, 287 (2003).

¹Prepared by LLNL under Contract DE-AC52-07NA27344.

Christopher Young
Lawrence Livermore National Laboratory

Date submitted: 05 Jul 2017

Electronic form version 1.4