

Abstract Submitted
for the MAR07 Meeting of
The American Physical Society

Investigation of the Direct Hydrogenation of Aluminum to Alane in Supercritical Fluids CRAIG JENSEN, University of Hawaii, SEAN MCGRADY, REYNA AYABE, University of Hawaii, BEN REDDY, University of New Brunswick — Alane, AlH_3 has many of the properties that are requisite for materials to be considered viable for onboard hydrogen storage applications. Most notably, it contains 10.1 wt% hydrogen and undergoes dehydrogenation at appreciable rates at temperatures below 100°C . However, the very low, ≥ 6 kJ/mol, enthalpy of dehydrogenation of AlH_3 prohibits subsequent re-hydrogenation through standard gas-solid techniques except at very high pressures or very low temperatures. The extremely low solubility of gaseous H_2 in conventional organic solvents also vitiates a solution-based approach. Re-hydrogenation of Al using a supercritical fluid potentially offers a workable approach since the fluid can act as a solvent, at the same time remaining completely miscible with permanent gases like hydrogen. Recently, it has been found that mixtures of NaH and Al can be hydrogenated to sodium alanate, NaAlH_4 under modest pressures and temperatures in supercritical fluids. We have now extended these studies to the hydrogenation of Al to AlH_3 . The results of these studies and experimental details will be reported.

Craig Jensen
University of Hawaii

Date submitted: 03 Dec 2006

Electronic form version 1.4