

Abstract Submitted
for the MAR08 Meeting of
The American Physical Society

Measurements of a dc-SQUID phase qubit using rf-reflectometry¹

R.M. LEWIS, University of Maryland, B.K. COOPER, S.K. DUTTA, T. A. PALOMAKI, HANHEE PAIK, A. PRZYBYSZ, H. KWON, J. R. ANDERSON, C. J. LOBB, F. C. WELLSTOOD — We performed measurements of a *Nb/AlOx/Nb* dc-SQUID phase qubit at 100 mK by monitoring the plasma frequency, f_p , of the readout/isolation junction. This qubit contains two Josephson junctions (JJ) separated by a 1.3 nH inductance; one JJ operates as a pure phase qubit, the second JJ isolates and reads out the qubit junction. When driving the isolation junction at 1.5 GHz, near f_p , current fluctuations in the SQUID loop cause fluctuations in f_p which appear in the sidebands of the reflected microwave power. At 100 mK we find an effective flux noise, $S_{\Phi}^{0.5}$ of $50 \mu\Phi_0/Hz^{0.5}$ at 1 Hz. The measurement bandwidth is about 10 MHz, the upper limit being set by the Q of the readout junction. We will discuss how the measurement performance depends on biasing parameters of each junction.

¹Funding from the Joint Quantum Institute and the NSA.

Rupert Lewis
University of Maryland

Date submitted: 27 Nov 2007

Electronic form version 1.4