Abstract Submitted for the MAR09 Meeting of The American Physical Society

EPR Study of SiC Defects Related to N_2 and O_2 Annealing. SARAH THOMAS, MARY ELLEN ZVANUT, University of Alabama at Birmingham — SiC is a promising replacement for Si in future high power, high temperature electronic devices. It is well known that the Si/SiO₂ interface in MOSFETs has electronically active defects, and recent work has shown the same is true for SiC. Our research focuses on identifying the cause and location of defects in thermally treated SiC substrates using EPR at 9.8 GHz. Samples underwent isochronal anneals from 400 to 1000 °C in high purity dry (<0.9 ppm H₂O) N₂ or O₂. Room temperature EPR spectra showed two defects, defect A and defect B, with line-widths of 4G and 10G, respectively. The temperature dependence was similar for the N_2 and O_2 anneals until 800 $^{\circ}$ C, when the concentration of defect A, which stayed constant in N₂, decreased in O_2 . In both ambients defect B was eliminated, and it was determined that this defect was due to cutting. That the amount of defect A decreased during the O_2 anneals, but not during the N_2 , suggests that oxidation, perhaps through etching, removes the signal. During the talk we will compare the results of oxidation and reactive ion etching studies, as these will give a better understanding of the location of defect A.

> Sarah Thomas University of Alabama at Birmingham

Date submitted: 21 Nov 2008

Electronic form version 1.4