

Abstract Submitted
for the MAR10 Meeting of
The American Physical Society

Flame Retardant Polyelectrolyte-Nanoclay Layer-by-Layer Assemblies on Cotton¹ GALINA SUKHONOSOVA, YU-CHIN LI, JAIME GRUNLAN, Texas A&M University — Thin composite films of branched polyethylenimine (BPEI) and Laponite clay platelets were prepared using layer-by-layer assembly. Film thickness was tailored by altering the pH of the aqueous mixtures used to deposit these films, resulting in growth that ranged from 0.5 to 5 nm per bilayer. In all films, the clay platelets are uniformly deposited and look analogous to a cobblestone path in atomic force microscopy (AFM) surface images. These thin coatings were deposited onto cotton fabric and the fabric has significantly more char left after burning than the uncoated fabric. Thermogravimetric analysis (TGA) results reveal that fabric coated with 10-bilayers of BPEI-Laponite produces up to 6 wt% char at 500 ° C, which is almost an order of magnitude greater than untreated fabric. This study demonstrates that polymer-clay assemblies could improve the thermal stability of cotton and may be useful for fire safety applications.

¹The authors want to acknowledge the Building and Fire Research Laboratory (BFRL) at the National Institute of Standards and Technology (NIST) for the financial support of this work. The USDA SRRC provided cotton fabric and assistance with fabric testing.

Jaime Grunlan
Texas A&M University

Date submitted: 18 Nov 2009

Electronic form version 1.4