

Abstract Submitted  
for the MAR11 Meeting of  
The American Physical Society

**Measurement of the shear modulus of single-layer graphene<sup>1</sup>**

THOMAS METCALF, Naval Research Laboratory, XIAO LIU, JEREMY ROBINSON, KEITH PERKINS, BRIAN HOUSTON — We have measured the shear modulus of large area (2mm × 5mm), single-layer (90–95%) polycrystalline graphene sheets and found values consistent with theoretical predictions of  $G=200$  GPa. The graphene was grown by chemical vapor deposition onto a copper foil and subsequently transferred onto a mechanical resonator known as a double-paddle oscillator (DPO). DPOs are fabricated from single-crystal, 0.3mm thick silicon wafers, and have a torsional vibratory mode at 5500 Hz which has a very large quality factor,  $Q = 5 \times 10^7$ , at low ( $< 10$  K) temperatures, giving the DPO a high sensitivity to a film deposited on its torsional element. Such a film increases the (lumped-element) spring constant of the resonator, and the film's shear modulus can be deduced from the subsequent resonant frequency shift.

<sup>1</sup>Work supported by the Office of Naval Research

Thomas Metcalf  
Naval Research Laboratory

Date submitted: 18 Nov 2010

Electronic form version 1.4