

Abstract Submitted
for the MAR15 Meeting of
The American Physical Society

Model for Charge Injection with Electron Beams into Highly Disordered Insulating Materials¹ JOHN DENNISON, Utah State University, ALEC SIM, Irvine Valley College, GREG WILSON, Montana State University — The Walden-Wintle model for charge injection and transport through highly disordered insulating materials has been extended to include charge injection with a charged particle beam. The original model is applicable to charge injection in a dielectric material from a pair of electrodes in a parallel-plate geometry. It provides a versatile approach to predict the time-dependent current at a rear grounded electrode and the incident surface voltage, as the injection current density evolves over time with the development of a space charge barrier near the injection electrode. The Walden-Wintle model has been applied to many standard cases including Fowler-Nordheim injection, Schottky injection, space charge limited injection, and various tunneling mechanisms. The present model modifies the approach to include electrode-less charge injection via a charged particle beam, along with concomitant effects for the injection current, surface voltage, and electron emission as a charge is built up in the insulator. The approach is equally valid for near-surface injection and for bulk injection of both non-penetrating and penetrating radiation. The results are based on our dynamic emission model for electron emission yields dependent on accumulating charge in both the positive and negative charging regimes.

¹Supported through funds from NASA GSFC and a Senior Fellowship from the National Research Council and AFRL

John Dennison
Utah State University

Date submitted: 14 Nov 2014

Electronic form version 1.4