

Abstract Submitted  
for the MAR16 Meeting of  
The American Physical Society

**Coplanar waveguide flux qubit suitable for quantum annealing<sup>1</sup>**

CHRIS QUINTANA, UC Santa Barbara, YU CHEN, D. SANK, D. KAFRI, A. MEGRANT, T. C. WHITE, A. SHABANI, R. BARENDTS, Google, Santa Barbara, B. CAMPBELL, Z. CHEN, B. CHIARO, A. DUNSWORTH, UC Santa Barbara, A. FOWLER, E. JEFFREY, J. KELLY, E. LUCERO, J. Y. MUTUS, M. NEELEY, Google, Santa Barbara, C. NEILL, P. J. J. O'MALLEY, UC Santa Barbara, P. ROUSHAN, Google, Santa Barbara, A. VAINSENCHER, J. WENNER, UC Santa Barbara, J. M. MARTINIS, University of California and Google, Santa Barbara — We introduce the "fluxmon" flux qubit, designed with the goal of practical quantum annealing. The qubit's capacitance and linear inductance are provided by a coplanar waveguide on a low loss substrate, minimizing dielectric dissipation and in principle allowing for GHz-scale inter-qubit coupling in a highly connected tunable architecture. Utilizing a dispersive microwave readout scheme, we characterize single-qubit noise and dissipation, and present a simple tunable inter-qubit coupler. We discuss tradeoffs between coherence and coupling in a quantum annealing architecture.

<sup>1</sup>This work was supported by Google Inc. and by the NSF GRFP

Chris Quintana  
UC Santa Barbara

Date submitted: 06 Nov 2015

Electronic form version 1.4