

Abstract Submitted
for the MAR16 Meeting of
The American Physical Society

Electronic Transport of Encapsulated WSe₂ Fabricated by Pick-up of Pre-patterned hBN YAFANG YANG, Massachusetts Institute of Technology, KENJI WATANABE, TAKASHI TANIGUCHI, National Institute for Materials Science, Japan, PABLO JARILLO-HERRERO, Massachusetts Institute of Technology, MIT TEAM — We report high quality WSe₂ devices encapsulated between two hexagonal boron nitride (hBN) flakes using a pick-up method with etched hBN flakes. Previous work on graphene has shown that sample disorder can be greatly reduced via isolation from charge impurities in the substrate by means of encapsulation. However, the effect of encapsulation still remains unknown for dichalcogenides devices. Besides, the quality of contact to TMDs is also a critical factor limiting the transport performance of such devices. To measure the transport properties of dichalcogenide devices as a function of temperature, low resistance electrical contacts must be made to the material. To achieve this, we encapsulate few-layer WSe₂ in hexagonal boron nitride that has been patterned to allow ionic liquid doping of the contact region. This technique simultaneously protects the WSe₂ surface above and below, resulting in the highest mobility few-layer WSe₂ devices reported to date.

Yafang Yang
Massachusetts Institute of Technology

Date submitted: 23 Nov 2015

Electronic form version 1.4