

Abstract Submitted
for the MAR17 Meeting of
The American Physical Society

Active Flows on Trees ADEN FORROW, Massachusetts Institute of Technology, FRANCIS WOODHOUSE, University of Cambridge, JOERN DUNKEL, Massachusetts Institute of Technology — Coherent, large scale dynamics in many nonequilibrium physical, biological, or information transport networks are driven by small-scale local energy input. We introduce and explore a generic model for compressible active flows on tree networks. In contrast to thermally-driven systems, active friction selects discrete states with only a small number of oscillation modes activated at distinct fixed amplitudes. This state selection interacts with graph topology to produce different localized dynamical time scales in separate regions of large networks. Using perturbation theory, we systematically predict the stationary states of noisy networks and find good agreement with a Bayesian state estimation based on a hidden Markov model applied to simulated time series data on binary trees. While the number of stable states per tree scales exponentially with the number of edges, the mean number of activated modes in each state averages $\sim 1/4$ the number of edges. More broadly, these results suggest that the macroscopic response of active networks, from actomyosin force networks in cells to cytoplasmic flows, can be dominated by a significantly reduced number of modes, in stark contrast to energy equipartition in thermal equilibrium systems.

Aden Forrow
Massachusetts Institute of Technology

Date submitted: 11 Nov 2016

Electronic form version 1.4