

Abstract Submitted
for the MAR17 Meeting of
The American Physical Society

Electrochemical CO₂ Reduction via Gas-Phase Catholyte¹ BRITTANY E. CARTER, NATHAN T. NESBITT, LUKE A. D'IMPERIO, JEFFREY R. NAUGHTON, DAVE T. COURTNEY, STEVE SHEPARD, MICHAEL J. BURNS, Boston College, DAVID A. VERMAAS, WILSON A. SMITH, TU Delft, MICHAEL J. NAUGHTON, Boston College — Reducing CO₂ to CO through electrolysis, for the eventual conversion to hydrocarbons, provides a path towards utility-scale seasonal storage of renewable energy. Electrochemical reduction of CO₂ has previously been achieved using a two chamber system. The chambers are typically separated by a semipermeable Nafion membrane, with an oxygen evolution catalyst anode on one side, a gold cathode on the other, and a solution containing CO₂ on both sides. If instead, CO₂ gas was in the second chamber, the reaction should yield more CO formed from CO₂ at a given overpotential; this would result from the increased concentration of CO₂ at the cathode surface and more facile mass transport of the CO and CO₂. With liquid in one chamber and gas in the other, electrolysis is performed by integrating the cathode onto the semipermeable Nafion membrane. This membrane electrode assembly is fabricated via nanoimprint lithography (NIL), simultaneously achieving high active surface area and permeability. Challenges to the Nafion NIL process, and the performance of the system in CO₂ reduction, will be presented.

¹This material is based upon work supported by the National Science Foundation Graduate Research Fellowship under Grant No. (DGE-1258923).

Brittany Carter
Boston College

Date submitted: 11 Nov 2016

Electronic form version 1.4