Abstract Submitted for the MAR17 Meeting of The American Physical Society

Nonreciprocal Signal Routing in an Active Quantum Network¹

HAKAN E TURECI, ANJA METELMANN, Princeton Univ — As superconductor quantum technologies are moving towards large-scale integrated circuits, a robust and flexible approach to routing photons at the quantum level becomes a critical problem. Active circuits, which contain driven linear or non-linear elements judiciously embedded in the circuit offer a viable solution. We present a general strategy for routing non-reciprocally quantum signals between two sites of a given lattice of resonators, implementable with existing superconducting circuit components. Our approach makes use of a dual lattice of superconducting non-linear elements on the links connecting the nodes of the main lattice. Solutions for spatially selective driving of the link-elements can be found, which optimally balance coherent and dissipative hopping of microwave photons to non-reciprocally route signals between two given nodes. In certain lattices these optimal solutions are obtained at the exceptional point of the scattering matrix of the network. The presented strategy provides a design space that is governed by a dynamically tunable non-Hermitian generator that can be used to minimize the added quantum noise as well.

¹This work was supported by the U.S. Army Research Office (ARO) under Grant No. W911NF-15-1-0299

Hakan Tureci Princeton Univ

Date submitted: 11 Nov 2016 Electronic form version 1.4