

Abstract Submitted  
for the DAMOP07 Meeting of  
The American Physical Society

Sorting Category: 5.3 (T)

### Quantum Simulation Circuits for Sparse Hamiltonians<sup>1</sup>

NATHAN WIEBE, BARRY SANDERS, The University of Calgary —  
In 1982, Feynman suggested a quantum computer would efficiently simulate quantum systems and illustrated this concept with Heisenberg chains (Int. J. Theor. Phys, 21, 467), which are difficult to solve on a classical computer. Recently, building upon the work of Aharonov and Ta-Shma (Proc. 35th Annual ACM Symp. on Theory of Computing, 20-29), Berry, Ahokas, Cleve, and Sanders (arxiv:quant-ph/0508139) developed an algorithm that simulates state evolution for generic sparse time-independent Hamiltonians, which accounts for all resources and has a cost that is nearly linear in time. We present a quantum circuit protocol to implement this algorithm. Furthermore we discuss the adaptation of this scheme for a broad class of time-dependent Hamiltonians.

<sup>1</sup>We would like to acknowledge support from CIAR, MITACS, NSERC, ICORE, ARC, and General Dynamics.

- Prefer Oral Session  
 Prefer Poster Session

Nathan Wiebe  
nwiebe@qis.ucalgary.ca  
The University of Calgary

Date submitted: 02 Feb 2007

Electronic form version 1.4