

Abstract Submitted
for the DFD06 Meeting of
The American Physical Society

Sorting Category: 10. (T)

On the stabilization of bluff-body wakes by low-density base bleed¹ CARLOS MARTINEZ-BAZAN, ALEJANDRO SEVILLA, Dpto. de Ingenieria Mecanica y Minera, Universidad de Jaen (Spain), FLUID MECHANICS TEAM — Base bleed is a simple and well-known means of stabilizing bluff-body wakes at supercritical Reynolds numbers. In the present research we consider a generalization of previous works by studying the effect of the bleed-to-freestream density ratio, $S = \rho_b/\rho_\infty$, on the stability properties of the wake behind an axisymmetric, slender body with a blunt trailing edge. Since a lower density in the slow stream is known to inhibit absolute instability, here we restrict our attention to the case of light bleed fluid, $S < 1$. This mechanism is shown to inhibit the wake for values of the bleed coefficient, defined as the bleed-to-freestream velocity ratio $C_b = u_b/u_\infty$, smaller than those obtained in the homogeneous case of $S = 1$. Our approach consists of obtaining the basic, axisymmetric flow by integration of the full set of Navier-Stokes and species conservation equations in cylindrical coordinates, and calculating its linear, local, spatio-temporal stability downstream of the body base. The analysis predicts a critical bleed coefficient C_b^* , which decreases with the density ratio according to the linear law $C_b^* \simeq 0.01 + 0.05 S$ for $0.1 \leq S \leq 1$.

¹This work was supported by project #DPI2005-08654-C04-01.

Prefer Oral Session

Prefer Poster Session

Dpto. de Ingenieria Mecanica y Minera, Universidad de Jaen (Spain)

Carlos Martinez-Bazan

cmbazan@ujaen.es

Date submitted: 25 Jul 2006

Electronic form version 1.4