

Abstract Submitted  
for the DFD06 Meeting of  
The American Physical Society

Sorting Category: 45. (E)

**Power dissipation and fluidization in a vibrated/stirred granular flow** JAMES GILCHRIST, KENNETH FORD, HUGO CARAM, Department of Chemical Engineering, Lehigh University — We investigate flow of powders within a model high shear granulation process. High shear granulators typically produce flow by sweeping a pitched bladed under a granular bed at high rotation rates, providing both fluidization from upward lift from fast moving blades and flow in a circular motion. In our experimental setup, we partially decouple the fluidization and circulation by independently vibrating and stirring a deep granular bed. Without stirring, vibration begins to fluidize the bed when the Froude number,  $Fr > 1$ . By attaching an accelerometer to the vessel, we measure the resulting time of flight. The deep granular bed primarily behaves as a solid mass at moderate  $Fr$ , and we compare the accelerometer data to a simple model of a bouncing mass on a spring. The stirring mechanism allows measurement of the power required to maintain a constant rotation rate. Without vibration, the power draw is linearly related to the rotation rate. At high  $Fr$ , the power requirements for stirring the fluidized bed decrease dramatically. At intermediate  $Fr$ , we observe a transition between dense granular flow and fluidized granular behavior with increased vibration and stirring by monitoring the power requirements for stirring. This transition marks the boundary between dense granular flow and fluidized granular flow, and suggests the degree to which stirring influences bulk fluidization.

Prefer Oral Session  
 Prefer Poster Session

James Gilchrist  
gilchrist@lehigh.edu

Date submitted: 07 Aug 2006

Electronic form version 1.4