

Abstract Submitted
for the DPP05 Meeting of
The American Physical Society

Sorting Category: 5.6.2 (E)

ECH at DIII-D¹ J. LOHR, I.A. GORELOV, D. PONCE, J.F. TOOKER, R.W. CALLIS, General Atomics, K. KAJIWARA, Oak Ridge Institute for Science Education, R. ELLIS, Princeton Plasma Physics Laboratory — The gyrotron installation on the DIII-D tokamak is being upgraded with the acquisition of three 110 GHz, 1.0 MW, 10 s gyrotrons having cryogen-free magnets. In addition to these gyrotrons, which will have diode geometry, a single stage depressed collector prototype gyrotron, also operating at 110 GHz, but capable of generating in excess of 1.0 MW at increased efficiency is being tested to maximum parameters. A number of specialized system components are being developed to accommodate the increased output power of this tube. The ultimate system will generate up to 5.5 MW for experiments, with injected power in excess of 4.0 MW. Fast scanning of the injection angles, improved control of the high voltage power supplies, more flexible fault processing capability, better sweeping of the electron beam over the gyrotron collectors and enhanced control of the output power are being implemented.

¹Work supported by U.S. DOE under DE-FC02-04ER54698, DE-AC05-76OR00033, and DE-AC02-76CH03073.

Prefer Oral Session
 Prefer Poster Session

J. Lohr
lohr@fusion.gat.com

Date submitted: 21 Jul 2005

Electronic form version 1.4