

Abstract Submitted  
for the DPP06 Meeting of  
The American Physical Society

Sorting Category: 5.6.2 (E)

**Density Control Using the New Divertor Pumping  
Configuration in DIII-D**<sup>1</sup>

T.W. PETRIE, M.A. MAHDAVI, N.H. BROOKS, P.M. ANDERSON, J.R. FERRON, C.M. GREENFIELD, A.W. HYATT, T.C. LUCE, C.J. MURPHY, C.C. PETTY, M.R. WADE, W.P. WEST, GA, C.J. LASNIER, LLNL, R.J. COLCHIN, ORNL, J.G. WATKINS, SNL — The lower divertor of the DIII-D vacuum vessel has been modified to improve density control in symmetric double-null (DN), high triangularity plasmas. Achieving good density control is an important component in the effort to demonstrate fully non-inductive current drive in DN “AT” plasmas. With three independently-controlled divertor cryopump systems, particles can be exhausted from both outer divertor targets (lower and upper), as well as from the upper inner target. Particle pumping thus can be maintained, even as the up/down balance in the DN is varied. Experimental results using the new divertor show an additional 7 Torr-l/s is exhausted at moderate density in a balanced DN configuration. This result is in good agreement with a design prediction of 6 Torr-l/s at a similar density. Examples of density control in several plasma operating regimes are presented.

<sup>1</sup>Work supported by the U.S. DOE under DE-FC02-04ER54698.

Prefer Oral Session  
 Prefer Poster Session

Tom Petrie  
petrie@fusion.gat.com  
General Atomics

Date submitted: 21 Jul 2006

Electronic form version 1.4