

Abstract Submitted  
for the SHOCK05 Meeting of  
The American Physical Society

**Strategies for Tuning the Reactivity of NanoEnergetic Materials**

ANAND PRAKASH, SOO KIM, ALON MCCORMICK, MICHAEL ZACHARIAH,  
University of Maryland — Nanostructured fuel/oxidizer composites are being looked upon as a possible approach to enhance energy release rates. Here we report on two approaches to moderate/tune reactivity. In the first example we accelerate reactivity. The method is based on electrostatically enhanced assembly to promote the preferential arrangement of aluminum (fuel) nanoparticles with iron oxide (oxidizer) nanoparticles in the aerosol phase. Two unipolar chargers are employed to generate oppositely charged aluminum and iron oxide particles, which enhance the formation of intimately interconnected nanocomposite energetic materials. The results of burning tests and thermal analysis using differential scanning calorimetry (DSC) showed that aluminum/iron oxide nanocomposite aerosol materials synthesized by bipolar assembly had burning rates that are a factor of 10 higher than those produced by random Brownian coagulation. In a second approach we employ a very reactive oxidizer (Potassium permanganate;  $\sim 150$  nm) and create a less reactive shell (Iron oxide). The measured reactivity for a nano-Al/composite oxidizer could be varied by more than a factor of 10 as measured by the pressurization rate in a closed vessel (Psi/microsecond), by changing the coating thickness of the iron oxide. The composite oxidizer nanoparticles were synthesized by a new aerosol approach, where the non-wetting interaction between iron oxide and molten potassium permanganate aids the phase segregation of a nanocomposite droplet into a core-shell structure.

Michael Zachariah  
University of Maryland

Date submitted: 27 May 2005

Electronic form version 1.4