

Abstract Submitted
for the SHOCK13 Meeting of
The American Physical Society

Investigating iron material strength during phase transitions using Rayleigh-Taylor growth measurements¹ CHANNING HUNTINGTON, JON BELOF, KERRI BLOBLAUM, ROB CAVALLO, NATALIE KOSTINSKI, BRIAN MADDOX, MARK MAY, HYE-SOOK PARK, CHRISTOPHER PLECHATY, SHON PRISBREY, BRUCE REMINGTON, ROBERT RUDD, DAVID SWIFT, RUSSELL WALLACE, MICHAEL WILSON, Lawrence Livermore National Laboratory — A solid-solid phase transition between the bcc (α) and hcp (ϵ) lattice structures in iron is known to occur as the material is compressed. When kept below its melting point, an effective increase in the macroscopic strength of the material accompanies this phase transition. Understanding the strength of iron throughout the deformation process is important for improving models of planetary structure, including interpretation of seismic measurements on Earth. To explore iron strength at high pressures and strain rates, we have performed experiments at the OMEGA laser. The laser drive produces a pressure near 1 Mbar on a thin Fe disk with a sinusoidal ripple pattern imposed on its face. The ripples seed the Rayleigh-Taylor (RT) instability, the growth of which is suppressed by the material strength of the sample. The ripple amplitude is diagnosed with x-ray radiography, and their growth is compared to values from simulations using different material strength models. This work will be compared to previous, similar experiments at 0.1 – 0.3 Mbar pressures (J. Belof et al., AIP Conf. Proc. 2012).

¹This work was performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344.

Channing Huntington
Lawrence Livermore National Laboratory

Date submitted: 22 Feb 2013

Electronic form version 1.4