

Abstract Submitted  
for the SHOCK17 Meeting of  
The American Physical Society

**Measurements of Rayleigh-Taylor growth in solid and liquid copper in the Mbar regime**<sup>1</sup> J. M. MCNANEY, A. ARSENLIS, C. M. HUNTINGTON, H.-S. PARK, S. PRISBREY, B. A. REMINGTON, D. C. SWIFT, C. E. WEHREBERG, Lawrence Livermore Natl Lab — Face-on radiographic measurements of ripple growth in solid and liquid copper have been performed at the OmegaEP laser facility. Pre-imposed ripples of 80m wavelength were accelerated by the stagnation of a releasing shocked polyimide “reservoir” which was directly driven by 4-9kJ of laser energy. The state of the copper was varied from solid to liquid by increasing the initial shock amplitude of the loading wave from below to above the Hugoniot shock-melting limit. A comparison with 2-dimensional hydrodynamic simulations indicates that growth in the solid phase is consistent with a strength roughly 1-3x that predicted by the commonly used Steinberg-Guinan model while growth in the liquid phase is consistent with little or no material strength.

<sup>1</sup>This work was performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344

James McNaney  
Lawrence Livermore Natl Lab

Date submitted: 24 Feb 2017

Electronic form version 1.4