

Abstract Submitted
for the SHOCK19 Meeting of
The American Physical Society

Measurements of shock sensitivity in a damaged explosive using a small-scale gap test¹ NICK CUMMOCK, Purdue University, CHRIS MOLEK, CHAD RUMCHIK, AFRL, STEVEN SON, Purdue University — The shock sensitivity of an explosive is often given in terms of the input pressure versus the corresponding run-distance to complete detonation. Plotted in log-log space, these are known as Pop-plots. In this work, small cylindrical samples of less than 0.5 g of explosive are used in a small-scale gap test to determine the run-distance as a function of pressure in PBX 9501 at varying initial densities, which are compared to thermally damaged samples. In this set of experiments, the L50, or pressure input at which 50% of the samples will initiate is determined for pellets of length equal to 6 mm and 3 mm, where the pellet length is taken as the run distance for the L50 pressure. Differences in shock sensitivity as shown by Pop-plots are shown. Further work involving isolation of the mechanisms influencing the change in shock sensitivity, such as porosity shifts, changes in particle size, and solid phase changes is considered.

¹Author N.R.C. wishes to acknowledge support from the Science, Mathematics and Research for Transformation (SMART) Scholarship for Service Program under grant No.2016-99534.

Nick Cummock
Purdue University

Date submitted: 26 Feb 2019

Electronic form version 1.4