

Abstract Submitted  
for the APR06 Meeting of  
The American Physical Society

**A Gyrotron-Powered Pellet Accelerator for Tokamak Fueling<sup>1</sup>**

P.B. PARKS, F.W. PERKINS, General Atomics — A novel pellet acceleration concept [1] using microwave power from MW gyrotron sources has been developed that could pave the way for high-speed  $>3$  km/s inner-wall pellet injection on ITER-class tokamaks. The concept is based on the principle of a gun, where a high-pressure propellant gas drives the projectile down the barrel. In the proposed concept, the high gas pressure is created by evaporative explosion of a composite “pusher” medium attached behind the DT fuel pellet. The pusher consists of micron-sized conducting particles, (Li, Be, C) embedded uniformly in a D<sub>2</sub> ice slug with  $<5\%$  volume concentration, thus facilitating microwave energy absorption by dissipation of eddy currents flowing within the conducting particles only. Microwave power is delivered to the pusher along a waveguide, which also serves as the pellet launch tube. A scaling law predicts that a pellet of mass  $M$  accelerated over a distance  $L$  reaches a velocity  $v \cong (PL/M)^{1/3}$ , where  $P$  is the gyrotron power. [1] P. Parks & F. Perkins, US patent application “Microwave-Powered Pellet Accelerator,” No. 11/256/662, October 21, 2005.

<sup>1</sup>Work supported by the US DOE under DE-FG03-95ER54309.

P.B. Parks

Date submitted: 13 Jan 2006

Electronic form version 1.4