

Abstract Submitted
for the DFD10 Meeting of
The American Physical Society

Time-evolution and time-scales of topological structures in a turbulent boundary layer through conditional mean trajectory analysis¹

CALLUM ATKINSON, Laboratory for Turbulence Research in Aerospace and Combustion, Monash University, SERGEI CHUMAKOV, IVAN BERMEJO-MORENO, Center for Turbulence Research, Stanford University, XIAOHUA WU, Department of Mechanical Engineering, Royal Military College of Canada, JULIO SORIA, Laboratory for Turbulence Research in Aerospace and Combustion, Monash University — The Lagrangian evolution of the invariants of the velocity gradient tensor in wall-bounded turbulence is examined using conditional mean trajectories (CMT). Fields from direct numerical simulations of a turbulent boundary layer developing over a flat plate with fully turbulent flow over a Reynolds number range of $Re_\theta = 730$ to 1954 are used to extract the CMT in the invariant space of the velocity gradient tensor (Q_A, R_A), the invariant space of the strain-rate tensor (Q_S, R_S) and the invariant space of the rate-of-rotation tensor (Q_W, R_W). CMT are considered for the full boundary layer, the log layer and the log and buffer layers. Results show a cyclic evolution of local topology. Associated time scales are extracted and compared with homogeneous isotropic turbulence.

¹Supported by CTR Summer Program and the Australian Research Council.

Callum Atkinson
Laboratory for Turbulence Research in Aerospace and Combustion,
Monash University

Date submitted: 09 Aug 2010

Electronic form version 1.4