

Abstract Submitted  
for the DFD13 Meeting of  
The American Physical Society

**Impact of particle laden drops onto surfaces of various wettability**

VIKTOR GRISHAEV, CARLO SAVERIO IORIO, Microgravity Research Centre, Université libre de Bruxelles, EP-CP165/62, B-1050, Brussels, Belgium, ALIDAD AMIRFAZLI, Department of Mechanical Engineering 425 LSB Bldg, York University, 4700 Keele St, Toronto, ON, M3J 1P3, Canada — Understanding characteristics of the impact of complex drops (liquid and solid particles) onto substrates is important for many applications, e.g. for additive manufacturing. Complex drops (diameter  $\approx 3.8$  mm) were produced using polyethylene microspheres dispersed in deionized water. Drop impact was investigated on substrates with different wettability (contact angles  $<5^\circ$  and  $95^\circ$ ) using high-speed cameras and image processing methods. By varying speed of the drops (1.7 to 3.7 m/s), diameter of the particles (200 and 500  $\mu\text{m}$ ) and particles volume fraction (0 to 35%), the influence of these variables on the impact dynamics of the drop and the distribution of particles after the impact was studied. For hydrophilic substrate, drops with 200  $\mu\text{m}$  particles are arranged in a ring after the impact. For hydrophobic substrate, drops can split into several drops depending on drop velocity, size and volume fraction of particles. Also, the dynamics of drop spreading was elucidated.

Viktor Grishaev  
Microgravity Research Centre, Université libre de Bruxelles,  
EP-CP165/62, B-1050, Brussels, Belgium

Date submitted: 01 Aug 2013

Electronic form version 1.4