

Abstract Submitted  
for the DPP07 Meeting of  
The American Physical Society

**Plasma Density Measurements within Tungsten Wire-Array Z-Pinches on the COBRA Accelerator**<sup>1</sup> JON DOUGLASS, RYAN MCBRIDE, KATE BELL, PATRICK KNAPP, JOHN GREENLY, SERGEI PIKUZ, TANYA SHELKOVENKO, DAVID HAMMER, Cornell University — The COBRA pulsed-power generator, with a nominal peak current of 1.1 MA and a minimum zero-to-peak rise-time of about 100ns, is being used to study the early phases of wire-array z-pinch development with a variety of diagnostics. Here we present the results of applying point-projection x-ray radiography to make accurate, high-resolution spatial and temporal measurements of the plasma density distributions in tungsten (W) wire-array z-pinch implosions. Density measurements are quantified by comparing x-ray transmission recorded on photographic films to transmission through W calibration steps of known thicknesses. Plasma density distributions as a function of time are presented for the coronal ( $10^{18}$ - $10^{20}/\text{cm}^3$ ), ablation ( $<10^{18}/\text{cm}^3$ ) and on-axis ( $<10^{19}/\text{cm}^3$ ) plasmas during the pre-stagnation phases of z-pinch dynamics (70-170 ns after the start of the current pulse). With this data set the time dependence of ablation velocity and corresponding mass ablation rate are addressed.

<sup>1</sup>This research was supported by the Stewardship Sciences Academic Alliances program of the National Nuclear Security Administration under DOE Cooperative agreement DE-FC03-02NA00057.

Jon Douglass  
Cornell University

Date submitted: 18 Jul 2007

Electronic form version 1.4