

Abstract Submitted
for the DPP07 Meeting of
The American Physical Society

Numerical Analysis of the 2D Newcomb Equations for the Resistive Wall Modes (RWMs)¹ J. SHIRAISHI, ORISE, M.S. CHU, General Atomics, S. TOKUDA, N. AIBA, JAEA, M. FURUKAWA, U. Tokyo — Stabilization of the RWM is one of the most important design issues for future reactors operated in the advanced tokamak regime. The MARG2D [1] stability code, which solves the 2D Newcomb equations [2], is extended to study the stability of the RWM. The linear dynamics of the perturbations in RWM obeys the functional [3] $\delta W_r = \delta W_p + \delta W_{IV} + \delta W_{OV} + D_w = 0$, where δW_p is the plasma potential energy, $\delta W_{IV(OV)}$ the vacuum magnetic energy inside (outside) the resistive wall, and D_w the energy dissipated in the resistive wall. In MARG2D, δW_p and δW_{OV} are given by bilinear functionals of the displacements and the perturbed magnetic field. δW_{IV} is described by a scalar potential and solved by the finite element method. Results from the MARG2D code are compared with those given in [3]. The solutions of the eddy current on the resistive wall will also be compared with new WKB solutions. [1] N. Aiba, *et al.*, Plasma Phys. Control. Fusion **46**, 1699 (2004). [2] S. Tokuda and T. Watanabe, Phys. Plasmas **6**, 3012 (1999). [3] M.S. Chu, *et al.*, Nucl. Fusion **43**, 441 (2003).

¹Supported by the US DOE under DE-AC05-76OR00033 and DE-FG03-95ER54309.

J. Shiraishi
ORISE

Date submitted: 21 Jul 2007

Electronic form version 1.4