

Abstract Submitted  
for the DPP07 Meeting of  
The American Physical Society

**Feasibility Studies of Off-Axis Neutral Beam Current Drive in DIII-D**<sup>1</sup> M. MURAKAMI, J.M. PARK, ORNL, T.C. LUCE, H.E. ST. JOHN, M.R. WADE, General Atomics, T.A. CASPER, LLNL — The objective of off-axis neutral beam (NB) current drive (CD) is to supplement the off-axis electron cyclotron current drive for development of steady state, advanced tokamak scenarios. A modification being considered is to tilt the present neutral beam lines (BL) by raising the source end of the BL by  $\approx 1.5$  m. The driven current is calculated using the TRANSP and ONETWO/Nubeam Monte-Carlo codes taking into account finite orbit effects. When the beam is injected in the same direction as the toroidal field, a wide but localized off-axis CD ( $\approx 40$  kA/MW at  $\rho = 0.5$  with FWHM of 0.45) is calculated. The normalized CD efficiency ( $\zeta = 0.22$ ) is comparable or somewhat better than electron cyclotron current drive. Sensitivities to fast ion diffusion and the use of the off-axis CD for scenarios with high steady-state performance in DIII-D will be discussed.

<sup>1</sup>Supported by the US DOE under DE-AC05-00OR22725, DE-FC02-04ER54698, and W-7405-ENG-48.

M. Murakami  
ORNL

Date submitted: 23 Jul 2007

Electronic form version 1.4