

Abstract Submitted
for the DPP11 Meeting of
The American Physical Society

The relation between upstream radial widths of n_e and T_e and outer target power width for H-mode discharges in DIII-D¹ P.C. STANGEBY, J.D. ELDER, U. Toronto, J.A. BOEDO, UCSD, M.A. MAKOWSKI, C.J. LASNIER, LLNL, A.W. LEONARD, GA — For H mode discharges in DIII-D, the relation between the power width at the outer target, $\lambda_{q_{target}}$, and the radial profiles near the outside midplane is in somewhat better agreement with flux-limited (weak collisionality) electron parallel heat conduction, $q_{\parallel} \propto n_e T_e^{3/2}$, i.e. $\lambda_{q_{target}}^{flux-lim} = [3/(2\lambda_{T_e}^{up}) + 1/\lambda_{n_e}^{up}]^{-1}$, than Spitzer (collisional) electron parallel heat conduction, $\lambda_{q_{target}}^{Spitzer} = (2/7)\lambda_{T_e}^{up}$. It appears that cross-field transport is the basic controlling process of SOL widths, manifesting itself most directly in upstream widths, with parallel transport and volumetric losses in the SOL/divertor then controlling the relation between upstream and target widths. For an initial data set of three discharges it was found that $\lambda_{q_{target}}^{measured}/\lambda_{q_{target}}^{flux-lim} = 0.93, 0.90, 1.00$ while $\lambda_{q_{target}}^{measured}/\lambda_{q_{target}}^{Spitzer} = 1.32, 0.71, 1.21$. Further results will be reported for discharges in upcoming experiments. We find that for DIII-D H-mode shots, the strongest dependence for $\lambda_{q_{target}}^{measured}$ is I_p^{-1} . The separate contributions of $\lambda_{n_e}^{up}, \lambda_{T_e}^{up}$ to the observed I_p scaling is assessed.

¹Supported by US DOE under DE-FG02-07ER54917, DE-AC52-07NA27344 and DE-FC02-04ER54698.

P.C. Stangeby
U. Toronto

Date submitted: 25 Jul 2011

Electronic form version 1.4