

Abstract Submitted
for the DPP12 Meeting of
The American Physical Society

Temperature measurements along the principal Hugoniot for 0.2g/cc aerogel foam¹ JOHN BENAGE, MARTIN TACCETTI, SHENGNIAN LUO, NICK LANIER, KATERINA FALK, DEREK SCHMIDT, SCOTT CROCKETT, CHRIS FRYER, Los Alamos National Laboratory — Aerogel (SiO₂) foams are used in a variety of HED experiments such as radiation flow experiments and more recently as a low-density shock standard for WDM equation of state experiments. Many of these experiments can be sensitive to the equation of state (EOS) of the foam. Despite recent very successful Hugoniot measurements of 0.2 g/cc aerogel foam, the temperature of these foams at a given pressure has not been measured and many EOS models for foams ignore important physics, thus predicting very different temperatures for a given condition. We have completed a set of temperature measurements of 0.2 g/cc aerogel foam shocked along the principal Hugoniot from 100 to 400 GPa. The experiments were done using 12 beams at the Omega laser facility to launch strong steady shocks into the foam targets. The temperature of the shocked foam was determined from measurements using the streaked optical pyrometer (SOP). The range of pressures covered established the behavior of the temperature through the important dissociation and initial ionization range. Equation of state models, where available, are compared to the data.

¹Work performed under the auspices of the Department of Energy.

John Benage
Los Alamos National Laboratory

Date submitted: 11 Jul 2012

Electronic form version 1.4