

Abstract Submitted
for the DPP12 Meeting of
The American Physical Society

OEDGE Assessment of Pressure and Power Balance Methods for Separatrix Identification¹ J.D. ELDER, P.C. STANGEBY, U. Toronto, A.W. LEONARD, B.D. BRAY, N.H. BROOKS, General Atomics, J.A. BOEDO, D.L. RUDAKOV, UCSD, J.G. WATKINS, Sandia National Laboratories, E.A. UNTERBERG, ORNL, C. LASNIER, LLNL — The OEDGE code is used to assess several methods of determining the upstream separatrix location. The inter-ELM phase of a well-diagnosed ELMing H-mode discharge is being used for this comparison. The OEDGE code utilizes 1D plasma fluid models calculated along the field lines on a 2D computational grid of a poloidal cross-section of the discharge magnetic geometry to produce a 2D model of the background plasma. Langmuir probe data at the targets are used as input to the 1D models. Additional diagnostic measurements, including Thomson scattering, reciprocating probe, divertor spectroscopy and infrared measurements of target heat flux, may be used to further constrain the plasma background determined by OEDGE. This plasma background thus found, is then used to identify the location of the separatrix in the experimental data by comparing the upstream plasma profiles from OEDGE to the experimental measurements. The OEDGE result is then compared to the separatrix locations predicted using simple pressure balance and power balance considerations.

¹Work supported by US DOE under DE-FG02-95ER54309, DE FC02 04ER54698, DE-FG02 07ER54917, DE-AC04-94AL85000, DE AC05-00OR22725, and DE-AC52-07NA27344

David Elder
U. Toronto

Date submitted: 12 Jul 2012

Electronic form version 1.4