

Abstract Submitted
for the DPP13 Meeting of
The American Physical Society

Dust generation at interaction of plasma jet with surfaces¹

CATALIN TICOS, National Institute for Laser, Plasma and Radiation Physics, 077125 Bucharest, Romania, DORINA TOADER, NICOLETA BANU, ADRIAN SCURTU, National Institute for Laser, Plasma and Radiation Physics, 077125 Bucharest, Romania and University of Bucharest, Romania, MIHAI OANE, National Institute for Laser, Plasma and Radiation Physics, 077125 Bucharest, Romania — Coatings of W and C with widths of a few microns will be exposed to plasma jet for studying the erosion of the surface and detachment of micron size dust particles. A coaxial plasma gun has been built inside a vacuum chamber for producing supersonic plasma jets. Its design is based on a 50 kJ coaxial plasma gun which has been successfully used for accelerating hypervelocity dust. Initial shots were carried out for a capacitor bank with $C=12 \mu\text{F}$ and charged up to 2 kV. Currents of tens of amps were measured with a Rogowsky coil and plasma flow speeds of 4 km/s were inferred from high-speed images of jet propagation. An upgrade consisting in adding capacitors in parallel will be performed in order to increase the energy up to 2 kJ. A coil will be installed at the gun muzzle to compress the plasma flow and increase the energy density of the jet on the sample surface. A CCD camera with a maximum recording speed of 100 k fps and a maximum resolution of 1024x1024 pixels was set for image acquisition of the plasma and dust. A laser system used to illuminate the ejected dust from the surface includes a laser diode emitting at 650 nm with a beam power of 25 mW.

¹The authors acknowledge support from EURATOM WP13-IPH-A03-P2-02-BS22.

Catalin Ticos
National Institute for Laser, Plasma and Radiation Physics,
077125 Bucharest, Romania

Date submitted: 12 Jul 2013

Electronic form version 1.4