

Abstract Submitted
for the DPP20 Meeting of
The American Physical Society

Design of First Magnetized Hohlräum-Driven Implosions on NIF¹

D. J. STROZZI, J. D. MOODY, H. SIO, B. B. POLLOCK, D. D. HO, C. A. WALSH, G. B. ZIMMERMAN, S. O. KUCHEYEV, Lawrence Livermore Natl Lab — The first magnetized, hohlraum-driven implosions on NIF – or any facility – are planned for the end of 2020. The goal is to demonstrate field compression in the implosion, following the MHD frozen-in law, which will be diagnosed by improved capsule nuclear performance (higher yield and temperature). These will be deuterium gas-filled capsules based on the “BigFoot” campaign, and use about 900 kJ of laser energy (about half of NIF’s maximum). To facilitate soak-through of the externally-imposed, predominantly axial field, especially against inward radial $\mathbf{J} \times \mathbf{B}$ motion, a hohlraum with much higher electrical resistivity than the typical gold or uranium is needed. A novel gold-tantalum alloy has been developed for this purpose, with the first shots using a 2:8 Au:Ta mixture (atomic). We present radiation-MHD modeling of this design with the Lasnex code. Based on this, we expect DD neutron yields $(2-4) \times 10^{13}$ and burn-weighted ion temperature of 3.5 – 4 keV, with an imposed 30 Tesla field. This should be 30-50% higher in yield, and 0.5 keV in T_{ion} , than an unmagnetized analog. The first two shots will vary the laser cone fraction (inner-beam vs. total power), to tune the implosion shape, and the third shot will be an unmagnetized repeat of one of these shots.

¹Prepared by LLNL under Contract DE-AC52-07NA27344 under the LDRD project SI-2020-002.

David Strozzi
Lawrence Livermore Natl Lab

Date submitted: 26 Jun 2020

Electronic form version 1.4