

Abstract Submitted
for the DPP20 Meeting of
The American Physical Society

Scenario development of ITER ELMy H-mode hydrogen plasma

EMMI THOLERUS, LUCA GARZOTTI, YURIY BARANOV, GERARD CORRIGAN, FLORIAN KOECHL, ELINA MILITELLO ASP, VASSILI PARAIL, CCFE, Culham Science Centre, Abingdon, Oxon, OX14 3DB, UK, DANIELA FARINA, LORENZO FIGINI, Istituto per la Scienza e Tecnologia dei Plasmi, CNR, Milan, Italy, DEREK HARTING, Institut für Energie- und Klimaforschung IEK-4, FZJ, TEC, 52425 Jülich, Germany, ALBERTO LOARTE, SIMON PINCHES, ALEXEI POLEVOI, ITER Org., Route de Vinon-sur-Verdon, CS 90 046, 13067 St. Paul-lez-Durance, France, HANS NORDMAN, PÄR STRAND, Association EURATOM-VR, Chalmers University of Technology, Göteborg, Sweden, ROBERTA SARTORI, Fusion For Energy Joint Undertaking, Josep Pla 2, 08019, Barcelona, Spain — Here we study the possibility for ITER ELMy H-mode operation in hydrogen plasma at 7.5MA/2.65T using up to 33MW NBI and 20 – 30MW ECH, intended for commissioning of the ELM control systems. Two strategies are considered to lower P_{L-H} : a) operation at low density, or b) introducing $\sim 10\%$ He (since this is observed to decrease P_{L-H} in JET [1]). The scenarios are modelled self-consistently using JINTRAC [2], developed by EUROfusion for integrated core (JETTO/SANCO/EDWM), edge and SOL/divertor modelling (EDGE2D/EIRENE). Results obtained so far indicate that stationary ELMy H-mode is indeed accessible, with and without 10% He, provided that the ECH power level is 30MW. [1] D.C. McDonald, *et al.*, EFDA-JET Report No. EFDA-JET-CP(10)08/24 (2011) [2] M. Romanelli, *et al.*, *Plasma and Fusion Research* **9**, 3403023 (2014)

Emmi Tholerus
Culham Science Centre

Date submitted: 30 Jun 2020

Electronic form version 1.4