

Abstract Submitted  
for the GEC18 Meeting of  
The American Physical Society

**Kinetic Spectra of the Planar Multipole Resonance Probe<sup>1</sup>**

MICHAEL FRIEDRICHS, Institute of Product and Process Innovation, Leuphana University, JENS OBERRATH, Institute of Product and Process Innovation, Leuphana University Lneburg, Germany — The planar multipole resonance probe is suitable for industrial plasma diagnostic purposes and consists of two half-disc electrodes, which can be integrated into the chamber wall of the reactor. Due to its minimal invasive character, inner plasma parameters can be monitored during the process. Based on a fluid model it is possible to determine the electron density from a detected resonance frequency in the measured spectrum. However, to monitor also the electron temperature an additional resonance parameter, e.g. the half-width of the resonance peak, is necessary. It is strongly influenced by kinetic effects, therefore a study of a kinetic model to obtain a relation between the half-width and the electron temperature is required. In this work such a kinetic model based on functional analytic methods and first spectra are presented.

<sup>1</sup>The authors gratefully acknowledge funding by the German Research Foundation (DFG) within the project OB 469/1-1

Michael Friedrichs  
Institute of Product and Process Innovation, Leuphana University

Date submitted: 14 Jun 2018

Electronic form version 1.4